


Plan View



Front View

Legend
△ : Fixed Point



* Magazine not included
* Tower light (optional)

Features

- ❖ Sturdy and stable design
- ❖ User friendly 'soft touch' LED membrane control panel
- ❖ Toggle level clamps provided for magazine alignment
- ❖ Pneumatic pusher's pressure regulated
- ❖ High throughput with short magazine change-over time
- ❖ SMEMA compatible

SPECIFICATIONS

| Description | This unit is used for loading or unloading of PCBs. |
|-------------------|--|
| PCB Magazine | Specify upon order |
| PCB Loading Time | 26 seconds max. (Loader) 20 seconds max. (Unloader) |
| Indexing Pitch | 1 - 4 (10 mm pitch) or specify |
| Power Source | 100, 230VAC 1Ph |
| Power Consumption | 550VA max |
| Air Pressure | 4 - 6 bar |
| Air Consumption | 10 ltr/min max |
| PCB Thickness | 0.4mm min |

| Size | Model No. | Machine Dimension (mm) L x W x H | Fixed Point to Front Dimension (X) | Weight (Approximately) |
|------|----------------------|-------------------------------------|---------------------------------------|---------------------------|
| M | NTM2000LM (Loader) | 1080 x 1355 x 1330 | 380 mm | 330 kg |
| L | NTM2000LL (Loader) | 1420 x 1680 x 1330 | 380 mm | 380 kg |
| M | NTM2000UM (Unloader) | 880 x 1350 x 1330 | 380 mm | 330 kg |
| L | NTM2000UL (Unloader) | 1140 x 1680 x 1330 | 380 mm | 360 kg |