


Plan View



Front View

Legend  
 △ : Fixed Point



\* Magazine not included  
 \* Tower light (optional)

## Features

- ❖ User friendly 'soft touch' LED membrane control panel
- ❖ First In First Out (FIFO), Last In First Out (LIFO), loader, unloader, reject stock and pass through operating modes
- ❖ Fast, smooth and precise indexing (frequency inverter controller)
- ❖ Pneumatic clamps provided for magazine alignment
- ❖ Pneumatic pusher's pressure regulated
- ❖ Threshold system provided
- ❖ Additional magazines buffering capacity available upon request
- ❖ SMEMA compatible

SPECIFICATIONS	
<b>Description</b>	This unit is used as a buffer between SMD machines or testers.
<b>PCB Magazine</b>	Specify upon order
<b>Cycle Time</b>	Average 20 seconds
<b>Indexing Pitch</b>	1 - 4 (10 mm pitch) or specify
<b>Power Source</b>	100, 230VAC 1Ph
<b>Power Consumption</b>	350VA max.
<b>Air Pressure</b>	4 - 6 bar
<b>Air Consumption</b>	15 ltr/min. max.
<b>PCB Thickness</b>	0.6 mm min.

Size	Model No.	Machine Dimension (mm) L x W x H	Fixed Point to Front Dimension (X)	Weight (Approximately)
M	NTM0600-M	1260 x 1165 x 1330	380 mm	200 kg
L	NTM0600-L	1560 x 1455 x 1330	380 mm	250 kg