


Plan View



Front View

Legend  
△ : Fixed Point



## Features

- ❖ Robust design
- ❖ Two belt segments
- ❖ Adjustable inclined angle ( $4^{\circ}$  -  $7^{\circ}$ ) or specify
- ❖ Variable speed control to synchronise with wave soldering machine
- ❖ PLC controlled (optional)
- ❖ SMEMA compatible

| SPECIFICATIONS           |                                                                                |
|--------------------------|--------------------------------------------------------------------------------|
| <b>Description</b>       | This unit is used for transferring of PCBs/pallets into the soldering machine. |
| <b>Conveyor Speed</b>    | 0.5 - 14 m/min.                                                                |
| <b>PCB Edge Support</b>  | 3 mm                                                                           |
| <b>Power Source</b>      | 100, 230VAC 1Ph                                                                |
| <b>Power Consumption</b> | 150VA max.                                                                     |
| <b>PCB Thickness</b>     | 0.6 mm min.                                                                    |

| Size | Model No. | Machine Dimension (mm)<br>L x W x H         | Fixed Point to Front<br>Dimension (X) | Weight<br>(Approximately) |
|------|-----------|---------------------------------------------|---------------------------------------|---------------------------|
| M    | NTM2300IM | 1000 x 535 x H1, H2<br>(specify upon order) | 50 mm                                 | 60 kg                     |
| L    | NTM2300IL | 1000 x 690 x H1, H2<br>(specify upon order) | 50 mm                                 | 70 kg                     |